



heatapp! gateway is the main communication interface for single room heat regulation. heatapp! gateway wirelessly sends and receives information to all radio components for control of the radiators (heatapp! drive), underfloor heating system (heatapp! floor), the electrical heaters (heatapp! single floor) and for room temperature measurement (heatapp! sense and heatapp! sense control) and serves as a message interface for heatapp! base/heatapp! base T2B and heatcon! EC.

Scope of delivery:

- heatapp! gateway
- Ethernet cable
- Power supply unit

| Article number: 9600200000 | |
|----------------------------|--|
| | |

| Technical data | | |
|-----------------------|-----------------------------|--|
| Installation | Table device | |
| Operating system | Linux | |
| Wireless system | Z-Wave, Static Controller | |
| Wi-Fi | 802.11b/g/n | |
| Connections | | |
| External | • USB 2.0 | |
| | RJ45 Ethernet | |
| Power supply | Power supply unit 5 V, 1 A | |
| Power consumption | 5 W | |
| Ambient conditions | | |
| Storage temperature | -25 +60 °C | |
| Operating temperature | -10 +50 °C | |
| Dimensions | 124 x 124 x 27.5 mm (LxBxH) | |
| Weight | 170 g | |
| Colour | Traffic white RAL 9016 | |