
 <p>Extension module EM - GBA</p> 	<p>heatcon! Extension module EM - GBA</p> <p>Function:</p> <ul style="list-style-type: none"> • Connection module when using more than 2 heatcon! EC <p>Attribute:</p> <ul style="list-style-type: none"> • Hat rail housing
<p>heatcon! Extension module EM - GBA</p> <p>Technical data</p>	<p>Article no.</p>
<p>Installation</p>	<p>Hat rail housing in the energy generator</p>
<p>Outlets</p>	<p>Device bus</p>
<p>Connection technology</p>	<ul style="list-style-type: none"> • Screw terminal connection • Plug contact
<p>Maximum cable length</p> <p>cable cross-section</p>	<p>100 m</p> <p>0,8 mm²</p>
<p>IP class</p>	<p>0</p>
<p>IP rating</p>	<p>IP00</p>
<p>Ambient conditions</p> <ul style="list-style-type: none"> • Storage temperature • Operating temperature 	<p>-25 ... +60 °C</p> <p>-10 ... +50 °C</p>
<p>Connections</p>	<ul style="list-style-type: none"> • 2 x device bus screw terminal • 2 x devicebus plug contact
<p>Standards</p>	<p>DIN EN 60730</p>
<p>Dimensions</p>	<p>35 x 90 x 61 mm (length x width x height) including hat rail</p>
<p>Colour</p>	<p>Grey</p>